



Model 6050



Economy General Purpose Industrial Accelerometer

<u>ITEM</u>	<u>PART No</u>	<u>DESCRIPTION</u>	<u>QTY</u>	<u>UNIT \$</u>	<u>EXT. \$</u>
1	9357242	General purpose industrial accelerometer. <u>Features</u> Splashproof construction Top 2-Pin MIL style connector 1/4-28 mounting stud <u>Specifications</u> Sensitivity: 100 mV/g (@ 100Hz, ±10%) Frequency Range:- 5 Hz - 10 kHz (±5%) 4 Hz - 12 kHz (±10%) 2 Hz - 20 kHz (±3dB) Amplitude Range: ±75 g peak Temperature Range: -40 to 121°C Dimensions: 1.515" h x 0.875" across flats Weight: 68 grams Sensors include: NIST Traceable Calibration, 1/4-28 Mounting Stud, User Manual and 1-Year Warranty	1	175.00	175.00
2	9356686-6	Cable, 2-Pin Right Angle or Top Entry, MIL/BNC 6ft molded splashproof	1	55.00	55.00
3	9356686-15	Cable, 2-Pin Right Angle or Top Entry MIL/BNC 15ft molded splashproof	1	75.00	75.00
4	9356687-15	Cable, 2-Pin Right Angle or Top Entry 15ft Braided with PVC shield	1	75.00	75.00

Terms & Conditions

DISCOUNT:	25-50 Units: Less 5%
	50+ Units: Call to discuss
DELIVERY:	\$10.00 Airbag
AVAILABILITY:	Ex Stock
GST APPLICABLE:	+10% GST has not yet been applied
WARRANTY:	12 months as per manufacturers standard
PAYMENT:	Visa/Mastercard
VALIDITY:	30 - days